

Vacuum Packaging machine **CV1000 Pro**



Vacuum packaging machine with automatic synchronized unloading of bags

Characteristics

- 100% in stainless steel construction.
- Automated opening and closing of the lid.
- Automatic lid closure: programmable or operated with hands-free system (foot sensor).
- Double grooved seal bars with programmable cut-off-seal.
- LED control panel with synchronizable printer.
- Equipment synchronizable with an automatic Shrink tank.



Compact equipment with the integrated 160m³/h Busch vacuum pump



TWIN option: two equipment fed by only one operator allow high production



Synchronizable packaging machine with two packaging lines and for complementary processes as the automatic shrinking and drying

Technical Data

Exterior dimensions	1180 x 850 x 1600 mm. (weidth xlongxhigh)
Chamber inner dimensions	1050 x 630 x 220 mm.
Vacuum pump	160 m3/h Busch 250m3/h Busch (optional - exterior)
Seal bars	A) 2 x 1.000 mm. (free distance 550 mm.) B) 1x900mm. + 1x550mm. C) 2 x 900 mm. + 1 x 550 mm. (optional)
Electric power	3'5 Kw
Electric connection	3F - 380V (optional 3F -220V)
Pneumatic connection	6 Bar
Weight	420 Kg (with 160m3/hBV Busch)

