

## Vacuum Packaging machine

# MEDIUM CV800



### Characteristics

- Construction 100% in stainless steel (aisi304)
- Technical methacrylate flat lid 50mm (optional oval lid)
- 2 seal bars in the chamber (possibility to install a 3rd and 4th bar)
- Double groove sealing system for double sealing of the bag
- Technical methacrylate lid, high strength and durability
- Easy and intuitive control panel
- Programmable vacuum level by sensor + extra time
- Time-programmable sealing level
- Automatic monitoring for vacuum pump maintenance
- Stop function button
- Stop + Sealed Button
- Easy maintenance and oil change
- Support videos for use and maintenance in [www.zermat.es](http://www.zermat.es)

## Technical data

Exterior dimensions	330 x 450 x 295 mm.
Chamber dimensions	280 x 310 x 85 mm.
Vacuum Pump	63 m <sup>3</sup> /h Busch 100m <sup>3</sup> /h Busch (optional)
Electrical power	3'5Kw
Electrical connection	3F - 380V (optional 3F -220V)
Seal bars standard	<b>Option 1:</b> 1 x 800mm + 1 x 550mm
Possibilities bar configuration: (without extra cost)	<b>Option 2:</b> 2 x 830mm bars <b>Option 3:</b> 2 x 550mm bars